

LARGE FLAT PANEL SWING ARM MOUNTS

FAQ

1. What is the difference between the PDR and PNR?

A The PDR extends over 37" from the wall, while the PNR extends 24-7/8".

2. How do I know if my screen is too small to use with PDR?

A The PDR is designed for 42" screens and larger. To ensure the mount will be completely hidden, your screen width should be greater than 40" and screen height should be greater than 25".

3. Is the PDR available as a universal solution?

A Yes. Simply order a PDR-U to receive a universal interface bracket with the unit. The PDR can also be ordered as a custom mount. See ordering steps below.

HOW TO ORDER

1. Determine which style mount will best suit your needs.

Note: flat panel displays smaller than 37" generally require a mount from our Small or Medium Flat Panel Display line. Check the cross-reference chart to verify.

2. For custom model number, look up your display in the cross-reference chart or on the website. Order PDR-xxxx, model number includes interface bracket.

3. For universal model number, order PDR-U, fits 90% of screen models.

4. Fax or e-mail your order to Customer Service at 877.894.6918 (domestic) or 952.894.6918 (international), or orders@chiefmfg.com.

CUSTOM OR UNIVERSAL

NEW

REACTION
SWING ARM MOUNTS

PDR™ DUAL SWING ARM WALL MOUNT

The ultimate home theater mount ideal for recessed applications, corners and viewing from all possible angles.

CU HE  37" EXTENSION

■ Solid Steel Construction

Designed with cast and steel components for unmatched strength.

■ Integrated Lateral Shift

Provides up to 4-1/2" of shift (114 mm) left or right of 16" centers.

■ Post-Installation Height Adjustment


Provides up to 3" (76 mm) of flexibility.

■ Mounting Guide System

Simple, one-man installation by hanging mount on two lag bolts.

■ Q-Latch™ Mounting System

- Offers quick connect/disconnect
- Secures display with a latching flag
- Includes integrated security with the addition of a padlock



■ Mount in Portrait or Landscape.

■ G-Force™ Gravity Centered Tilt

Provides fingertip tilt +5° to -15°, and ±2-1/2° of roll adjustment.

■ Integrated Security

Add a padlock to ensure the display is secure.

■ CableTrac™ System

Channeled cable management provides quick and easy routing of cables.

■ Ultimate Flexibility

Extreme range of motion for every viewing angle.

■ Aesthetic Design

- Curved arms provide a sleek look
- Available in black or silver to match screen

■ Multiple Ordering Options

- Custom interface for fast install
- Universal for stocking
- Wall mount without interface for pre-installation

■ Universal Option

Order PDR-U and get a PSB-U™ Universal Interface Bracket included.



SPECIFICATIONS

Depth From Wall*	2-7/8" (74 mm)
Extension from Wall	37-3/8" (95 cm)
Dimensions WxHxD	39-1/2" x 24-1/3" x 2-7/8" (100.3 x 61.8 x 7.4 cm)
Tilt/Roll	+5°, -15° / ±2-1/2°
Height Adjustment	3" (76 mm)
Lateral Shift	4-1/2" (114 mm) Left/Right
Color	Silver or Black
Weight Capacity	200 lbs (90.7 kg)

* Depth does not include interface bracket.

RECOMMENDED ACCESSORIES

	PAGE
PAC-140 Q-Clamp for added security	52
PAC-150* Video Conferencing Shelf	54
PAC-251* CPU/DVD/VCR Universal Adapter	50
PAC-300* Side Speaker Adapter	50
PAC-301* Center Channel Speaker Adapter	50
PAC-400* 90° Rotation Adapter	50

*Confirm that the combined weight of the screen and accessory will not exceed the mount's rated capacity. Note: Swing-arm mounts cannot be used with PAC-125, PAC-126 or ENS Lateral Shift accessories.